

LUBRICATION ENGINEERS®, INC.  
300 Bailey Avenue FORT WORTH, TX 76107

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

SUPPLIER:

Lubrication Engineers®, Inc.  
300 Bailey Avenue  
Fort Worth, TX 76107

EMERGENCY TELEPHONE NUMBERS.:

Company: (817) 834-6321  
In the event of an emergency spill, fire, or exposure—Call:  
Chemtec: (Within USA) (800) 424-9300  
(Outside USA—call collect) (703) 527-3887

CHEMICAL NAME AND SYNONYMS:

Not applicable

TRADE NAME AND SYNONYMS:

4059 H1 QUINPLEX® Penetrating Oil & Lubricant  
(Aerosol)

CHEMICAL FAMILY:

Hydrocarbon

FORMULA:

Not applicable

SECTION II - TYPICAL CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:

Light straw lubricant

VISCOSITY: @ 210°F, SUS  
Not applicable

@ 100°C, cSt  
Not applicable

ODOR:

Solvent odor

VISCOSITY: @ 100°F, SUS  
Not applicable

@ 40°C, cSt  
Not applicable

RELATIVE DENSITY:

(Air=1) >1

SOLUBILITY IN WATER:  
Negligible

PH: 6-8

MELTING POINT: °F

Not applicable

POUR POINT: °F

-17

BOILING POINT: °F

Unknown

FLASH POINT: °F (Method)  
45 (TCC)

BASE OIL: 400 °F (COC)

SPECIFIC GRAVITY: (H<sub>2</sub>O=1)

0.89

VAPOR PRESSURE:

Unknown

FLAMMABILITY CATEGORY PER 16 CFR 1500.45

Extremely flammable

SECTION III - INGREDIENTS

HAZARDOUS INGREDIENTS:

Carbon dioxide

<3.0

800 ppm

Unknown

Unknown

Isoparaffin

<30.0

400 ppm

Unknown

Unknown

Oil Mist (mineral)

<75.0

5mg/m<sup>3</sup>-TWA

Unknown

Unknown

NON-HAZARDOUS INGREDIENTS:

ADDITIVES AND/OR OTHER INGREDIENTS: This product is a mixture. The specific chemical identity of hazardous ingredients and non-hazardous ingredients, their C.A.S. numbers and their exact percent of composition are proprietary to Lubrication Engineers®, Inc. and are being withheld as Trade Secrets. The above listing of hazardous ingredients discloses the properties, approximate concentration and known toxicological effects of the hazardous ingredients. This material is an automotive/industrial lubricant with a low order of toxicity and irritancy. The product is formulated with ingredients that are not designated as harmful to the ozone.

REGULATORY INFORMATION:

SARA Title III: This product does not contain any chemical substance on the SARA Extremely Hazardous Substances list. If this product contains any chemicals that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372, they will be listed in the above HAZARDOUS INGREDIENTS section.

TSCA: This material is in compliance with the Toxic Substances Control Act (15 USC 2601-2629) and all components of this product appear on the Toxic Substance Control Act (TSCA) inventory list.

Clean Air Act: No ozone depleting chemicals listed in Title VI, Stratospheric Ozone Protection, Section 602 of the Clean Air Act are present or used in the manufacturing process of this product.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: °F (Method)

45 (TCC)

FLAMMABLE LIMITS: LEL UEL

Unknown

BASE OIL: 400 °F (C.O.C.)

EXTINGUISHING MEDIA:

Foam, dry chemical, water fog, or carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES:

Avoid possible accumulations of vapors at floor level, as vapor is heavier than air. Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Avoid possible bursting of aerosol can. Do not store where temperatures may exceed 120°F. Do not puncture or incinerate.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: (If Established)

Not established. Oil mist = 5mg/m<sup>3</sup>

400 ppm suggested

EFFECTS OF OVEREXPOSURE:

Inhalation and skin contact are the primary routes of entry. The product may cause dizziness and mild dermatitis upon prolonged contact and is expected to be an eye and lung irritant. Extended breathing of fumes may result in dizziness, nausea and headache. Any existing skin, eye, or lung irritation may be aggravated by direct contact. No components are listed on OSHA, I.A.R.C., or N.T.P. lists for carcinogens.

SECTION VI - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:

Flush immediately with water until irritation subsides.

SKIN CONTACT:

Wash affected skin area with mild soap and water.

INGESTION:

Do not induce vomiting. Contact a physician.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. Contact a physician.

SECTION VII - REACTIVITY DATA

STABILITY: (Thermal, Light, Etc.)

Stable

CONDITIONS TO AVOID:

Contact with nuclear radiation and strong oxidizing materials.

INCOMPATIBILITY: (Materials to avoid)

Strong oxidizing materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

Dense smoke; oxides of C, S, and P; hydrogen sulfide.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Treat as a petroleum oil spill.

WASTE DISPOSAL METHOD:

Used petroleum products may be recycled through re-refining processes.

SECTION IX - SPECIAL PROTECTION INFORMATION

EYE PROTECTION:

Sufficient to avoid direct contact.

SKIN PROTECTION:

Protective neoprene or plastic gloves may be desired.

RESPIRATORY PROTECTION:

Usually not needed in open, unconfined areas. If TLV is exceeded wear NIOSH approved self-contained breathing device or respirator.

VENTILATION:

Usually not needed in open, unconfined areas. In enclosed areas, sufficient ventilation to meet recommended TLV of 400 ppm. Ventilation is necessary at floor level as vapors are heavier than air.

OTHER:

Usually not needed.

SECTION X - SPECIAL PRECAUTIONS

Do not store above 120°F. Keep away from heat, sparks, open flames, and strong oxidants. Avoid eye contact and prolonged skin contact. Avoid breathing oil mists. Wash thoroughly after handling.

SECTION XI - HAZARD RATINGS

There are several recognized and accepted systems that assign hazard ratings to materials. Although this product has not been evaluated specifically against these systems, the ratings for the National Fire Protection Association (NFPA) and the National Paint and Coatings Association's Hazardous Material Identification System (HMIS) for the lubricant residue are:

	NFPA	HMIS
Health	2	2
Flammability	4	4
Reactivity	0	0